

Windows

**C language static analysis tool
SCANA**

User's Manual

(Ver. 1. 6. 0. 1)

1.	OVERVIEW.....	1
1.1.	Pre-Compile.....	1
1.2.	SYMBOL.....	3
1.3.	SYMBOL DETECTION.....	3
1.4.	DETECTION OF FUNCTION DEFINITION.....	4
1.5.	FUNCTION CALL DETECTION.....	4
1.6.	TOP LEVEL FUNCTION.....	4
1.7.	TAG JUMP.....	5
1.7.1.	Tag jump destination path name.....	5
1.7.2.	Tag jump line number.....	5
1.7.3.	Setting up the text editor.....	5
1.8.	Search string.....	6
1.9.	Listbox operation.....	6
1.10.	Maximum number of log lines.....	7
1.11.	Save analysis result log.....	7
2.	MAIN WINDOW.....	8
2.1.	MENU.....	10
2.1.1.	File Menu.....	10
2.1.2.	Set Menu.....	10
2.1.3.	Help Menu.....	11
2.1.4.	Language Menu.....	11
3.	SOURCE FILE SETTING.....	12
3.1.	Setting of source file.....	12
3.2.	Convert to Relative Path / Absolute Path.....	12
3.3.	Creating source text without comments.....	13
4.	PRE-COMPILE SETTING AND OPTION-SYMBOL / MACRO INFORMATION.....	14
4.1.	Header file precompilation.....	17
5.	TYPE NAME INFORMATION.....	18
6.	FUNCTION NAME INFORMATION.....	19
7.	FUNCTION CALL STRUCTURE.....	20
7.1.	Tooltip display of top function name.....	21
8.	FUNCTION NAME EXTRACTION FILTER.....	22
8.1.	SPECIFICATION OF SPECIFIC FUNCTION NAME.....	24
9.	SYMBOL CROSS REFERENCE INFORMATION.....	25
9.1.	Symbol -> Func.....	25
9.2.	Func -> Symbol.....	26
9.3.	Top Lvel Func -> Symbol.....	26
10.	SYMBOL EXTRACTION FILTER.....	27
10.1.	SPECIFIC SYMBOL.....	28
11.	SYMBOL COMFLICT INFORMATION.....	30
13.	EXECUTABLE WINDOWS VERSION.....	32
14.	DISCLAIMER.....	32

1. OVERVIEW

This application (hereinafter referred to as SCANA (Static C-language ANALizer)) is a static analysis tool of C language source program.

We already target C language programs that have been successfully built.

SCANA inputs the C language source program group and performs the following analysis processing.


- Precompile. (resolution of preprocessing statement - resolution of condition compilation (#if, #ifdef, # ifdef ...) or macro (#define))
- Extraction of option symbols ("_DEBUG" etc. of "# ifdef _ DEBUG") used at precompilation and listing of reference points.
- List of type names (typedef name, structure name, union name, enumeration name) and type name definition
- Extraction of macro names used at the time of precompilation and listing of definitions / references.
- A list of function names and a list of function definition points.
- Display function callingstructure.
- List of symbols such as variable names and list of symbol reference points.

1.1. Pre-Compile


When precompile (solution of preprocessing statement - condition compiling (#if, #ifdef, #ifndef · ...) and macro (#define) call) is performed, input the source file precompiled and output and analyze to hold.

When precompiling, it is necessary to give an appropriate include path and an option symbol for conditional compilation.

Flow when you do not precompile



Flow of precompile



※ when precompiling, please specify only include path of own program.

Giving an include path of the system may make it difficult to read the precompiled output source due to excessive macro resolution, or if the include file of the system is huge, analysis may become impossible due to insufficient memory.

If conditional compilation (#ifdef, #ifndef, #if, #elif, #else, #endif) is included in the source file or include file, only the part where the condition is "true" is output, and the part of the "false" condition (However, #ifdef, #ifndef, #if, #elif, #else, #endif are output even in false conditions)

In #ifdef, #ifndef, #if, #elif, #else, the operation result of the condition is displayed as "TRUE" or "FALSE".

In #endif, the line number of the corresponding #ifdef, #ifndef, #if is displayed.

(Example)

Source program	Pre-Compile result
<pre> 1 : #define A 10 2 : 3 : void func() 4 : { 5 : int x; 6 : 7 : #if A == 1 8 : x = 10; 9 : #elif A == 2 10 : x = 20; 11 : #elif A == 3 12 : x = 30; 13 : #elif A == 4 14 : x = 40; 15 : #elif A == 5 16 : x = 50; 17 : #elif A == 6 18 : x = 60; 19 : #else 20 : x = 99; 21 : #endif 22 : }</pre>	<pre> /* "D:\Temp\al\al.c" */ /* Include-Nest; Macro-Nest; SourceFile; LineNumber; */ /* 0; 0; a1.c; 1; */ /* #define A 10 */ /* 0; 0; a1.c; 2; */ /* 0; 0; a1.c; 3; */ void func() /* 0; 0; a1.c; 4; */ { /* 0; 0; a1.c; 5; */ int x; Boolean value of #if,#elif,#else /* 0; 0; a1.c; 6; */ /* 0; 0; a1.c; 7; */ // #if A==1 // --> FALSE /* 0; 0; a1.c; 8; */ /* 0; 0; a1.c; 9; */ // #elif A==2 // --> FALSE /* 0; 0; a1.c; 10; */ /* 0; 0; a1.c; 11; */ // #elif A==3 // --> FALSE /* 0; 0; a1.c; 12; */ /* 0; 0; a1.c; 13; */ // #elif A==4 // --> FALSE /* 0; 0; a1.c; 14; */ /* 0; 0; a1.c; 15; */ // #elif A==5 // --> FALSE /* 0; 0; a1.c; 16; */ /* 0; 0; a1.c; 17; */ // #elif A==6 // --> FALSE /* 0; 0; a1.c; 18; */ /* 0; 0; a1.c; 19; */ // #else // --> TRUE /* 0; 0; a1.c; 20; */ x=99; /* 0; 0; a1.c; 21; */ // #endif Corresponding- // --> 7 /* 0; 0; a1.c; 22; */ }</pre>

1.2. SYMBOL

The names of variable names, function names, type names, macro names ... etc. are collectively referred to as "symbols".

Symbol means the token of the following condition.

- 1) First character is alphabet, underscore (_), or dollar mark (\$) . . . (* 1)
- 2) Subsequent characters are alphabet, underscore (_), dollar mark (\$), or numbers (0 to 9)
- 3) As a special case, even when the above conditions are followed by a period (.) And a number (0 to 9) are also used as symbols ... (* 2)

- * 1: Although it is a violation under strict C language rules, some processing systems allow dollar marks.
- * 2: It is a violation under strict C language rules, but depending on the processing system, port description such as "P2.1" or "P10.0" is allowed.

However, an array variable treats a character string to which '[' is added like 'arr []' as a variable. Reserved names in C language ("if", "int", "static", "while", etc.) are not regarded as symbols.

1.3. SYMBOL DETECTION

It detects symbols from the source program and displays a list of symbols and cross-reference information of symbols. You can also set filters when extracting symbols

In the display of the reference position(file name, line number) of the symbol, if the symbol (variable) has been updated, it is indicated "*" at tail of the line number is updated. (* 1)

Example of displaying symbol cross reference information

```
336: pReadPoint ----- FABtxtSetValue ----- "R:¥_Product¥AirTerm¥AirTerm¥AirTerm¥src¥AjtAbsTxt.c" ----- < 1576
      1582 1589& 1595* 1602*
```

If the line number is followed by "&",
Indicates the address reference of the symbol ① . . ※2

If the line number is followed by "*",
Indicates that the symbol has been updated (②③) . . ※1

AjtAbsTxt.c

```
1589 hCtk = AjcCtkCreate(AJCTKFLG_INCSPACE, cbCtkAbTxtSetVal, (UX)&pReadPoint); ↓
1590 ↓
1591 do { ↓
1592     //----- 数值语句解析先頭位置設定 -----
1593     if (pAbstInfo->PfxStr[0] != 0) {
1594         if (p = MAjcStrStr(pLine, pAbstInfo->PfxStr)) {
1595             pReadPoint = p + MAjcStrLen(pAbstInfo->PfxStr);
1596         } ↓
1597     } else {
1598         break;
1599     } ↓
1600 } ↓
1601 else {
1602     pReadPoint = pLine;
1603 }
```

※1 The symbol "*" indicating that the symbol has been updated is a simple one and is detected under the following conditions.

- The words immediately before / after the symbol are "++" or "--"
- The word immediately after the symbol is "=" "+" "-" "*" "/" "%" "&" "|" "^" ">>" or "<<"

If the symbol is enclosed in parentheses or is a structure member, etc., the symbol update may not be recognized.

The following example does not recognize symbol (var) updates.

```
++p->var; (var) += 10; memset(&var, 0, sizeof var);
```

※2 The symbol "&", which indicates that the symbol is addressed, is simple and is detected under the following conditions.

- "&" Just before the symbol
- The two symbols before the symbol are "{", "(", "(", " or ")"

Therefore, other than address reference, it may be considered as address reference. In the following example, "&" is added even though it is not an address reference.

```
a = (b + c) & d; // "d" is considered as an address reference because it is arranged in the order ")" "&" "symbol"
```

1.4. DETECTION OF FUNCTION DEFINITION

Detects and extracts function definitions from the specified source program group.
 When the words are arranged in the following order, the definition of the function is recognized.




"Symbol" is recognized as a function name and "{" to "}" is recognized as the inside (function body) of the function.
 If parentheses ('(· · ·)' or '{· ··}') are nested, it is regarded as an arbitrary phrase group until nesting ends.
 The function name of the function definition detected in the source program is called "internal function".
 In contrast, a function not defined in the source program is called an "external function".

Function macros (macros with arguments) are also handled as external functions (if precompilation does not expand macros).
 You can also set filters when extracting internal function definitions.

1.5. FUNCTION CALL DETECTION

When words and phrases are arranged in the following order inside the function (function body), it is recognized as a function call.



At this time, "symbol" is recognized as the calling function name.
 Macro calls of function macros (macros with arguments) are also recognized as function calls.
 If the symbol matches the internal function name (that is, it is defined in the source program), it is recognized as a call to the internal function.
 If the symbol does not match the internal function name, it is recognized as a call to the external function.

<Caution>

In the case of a dynamic call with a function pointer etc., the variable name of the function pointer is recognized as the function name.
 In the following cases, "pFunc" is recognized as the calling function name.

<pre>int TopFunc(int flag, void (*pFunc)(int x, int y)) { . . . pFunc(10, 20); . . . }</pre>	<pre>void cbFunc(int x, int y) { . . . } void SubFunc(void) { TopFunc(0x1000, cbFunc); }</pre>
--	---

In the example above, calling TopFunc() from SubFunc() will pass the function pointer of cbFunc() as an argument and actually call cbFunc() from TopFunc(), but this is not recognized .


1.6. TOP LEVEL FUNCTION

The top level function means a function located at the vertex of the function call structure.
 For example, "TopFunc ()" is the highest level function in the sample source as shown below.

Sample Source

<pre>int TopFunc(int arg1, int arg2) { . . . sub1(); sub2(); . . . } void sub1(void) { sub1A(); }</pre>	<pre>void sub2(void) { . . . } void sub1A(void) { . . . }</pre>
--	--

Function call structure



Functions that are not called from any of the source programs are automatically recognized as "top level functions"

Functions starting with a specific character string can be additionally specified as "top level functions", or individually "top level functions" can be specified.

1.7. TAG JUMP

Double-click on the log window to open the tag jump destination file.

If you double-click while holding down the SHIFT key, open the precompile output file.

1.7.1. Tag jump destination path name

The part sandwiched by the double quote (") of the double clicked line becomes the path name of the tag jump destination file.

If there is no part sandwiched by double quotes (") on the double clicked line, search backward to find the path.

If the SHIFT key is pressed, the path name found is changed to the path name of the precompiled result.

1.7.2. Tag jump line number

When double-clicking on the numeric part, the number is regarded as the line number.

When double-clicking on a part other than a number, the part sandwiched by '<' and '>' of the double clicked line is regarded as the line number.

If there is no sandwiched part between '<' and '>' in the double clicked line, the line number = 1.

1.7.3. Setting up the text editor

In order to validate the line number of the tag jump destination, it is necessary to set the text editor.

From the "Set" → "Text Editor setting" menu, set the command line for starting the text editor as follows.


Text editor setting example

If you have not set the text editor, simply open the tag jump destination file.

(It is the same behavior as double-clicking on the file in Windows Explorer)

1.8. Search string

You can search for a string on the search result log window.
 To search for multiple character strings, separate them with delimiters.
 Specify the delimiter in the upper right corner of the log window.
 If you specify a delimiter, the separated spaces before and after each search string are ignored.
 When a string is found, it makes the string selected state (highlighted).



1.9. Listbox operation

Right click on the setting list box such as the source file and include path, the operation menu of the list box is displayed.

List box operation menu


Edit item	Edit the selected item (Add item if there is no selection item)
Select all	Make all items selected
Selection Release	Cancel selection of all items (Alternatively, double click on the list box)
Delete all selected items	Delete the selected item
Reset	Delete all items
Copy all	Copy all items to clipboard (* 1)
Copy selected item	Copies the selected item to the clipboard (* 1)
Paste	Add items from the clipboard (* 1)
Change to relative path	Convert the selected item to relative path (* 2)
Change to absolute path	Convert the selected item to an absolute path (* 2)

* 1: Each list box item corresponds to one line of text in the clipboard.

* 2: It is a relative path from "base folder". This menu will not be displayed if "base folder" is not set or in a list box that does not relate to the path name.


1.10. Maximum number of log lines

The maximum number of lines when logging the analysis result is set to 200,000 lines by default. If it is insufficient at 200,000 lines, right click on the log window, change "max lines" from the "Set Other" menu and press the "OK" button.



1.11. Save analysis result log

Press the  button to save the analysis result log. Press the  button to open the analysis result log folder. To display the saved logs in the past, select the text file to redisplay from "save text" in the log window and press the  button.  button sets the text encoding for saving / reading text with  or  button.




Pressing the  button deletes all logs saved in the past.

When saving with the  button, the date and time saved in the file name is included. To change the saved file name, open the folder with  button and change directly in Explorer. At this time, please do not change "SCAnaLog_" at the head.


2. MAIN WINDOW

When SCAN is started, the following main window will be displayed.





#	内容
①	Specify the source file or the top-level folder of the include file. It is the base position for automatically searching include files from this base folder, or changing path names to relative paths.
②	Select the tab and make various settings. These will be explained shortly.
③	Check if you want to pre-compile.
④	Check to display type name <ul style="list-style-type: none"> ・Type name list : Display type names list only ・Type definition list : Display type name and definition position(file name and line number)
⑤	Check to display a list of function names. <ul style="list-style-type: none"> ・ Internal function name list : Check this to display a list of internal function names ・ External function name list : Check this to display a list of external function names.
⑥	Check this to display a list of collected internal functions.
⑦	Check this to display the function call structure. <ul style="list-style-type: none"> ・ Include external functions in the call structure: Include calls to functions not defined in the source program.
⑧	Check this to display the collected symbol list.
⑨	Check this to display cross-reference information of symbols. <ul style="list-style-type: none"> ・ Symbol -> Function: Lists in which function and where each symbol is referenced. ・ Function → Symbol: Lists the symbols referenced by each function. ・ Upper-level function → Symbol: Lists the symbols referenced by the top-level function (including the calling subfunction)
⑩	Under the top-level function, list conflicting symbols.
⑪	Start analyzing C language source program. If the license has not been set and the trial period has already been exceeded, it will be grayed out. (That is, it can not be executed)
⑫	If you are analyzing C language source program, press Cancel button to abort processing.
⑬	Save current settings
⑭	Switches between the various setting screens (above screen) and the log screen.

When the “Execute” button is pressed or the screen is switched with the  button, the following screen appears.




*1: For example, when the “Function Call Structure” button is clicked, the following analysis result log window is displayed / hidden.




2.1. MENU

2.1.1. File Menu




Item	Content
Save	Save the current work name settings The same operation can be performed with the button (📁) in the upper right of the window.
Export setting	Export the settings to a file
Import setting	Import setting contents from file
Text Encode	Encode settings of input / output files, such as source files (* 1)
Exit	Quit the program

* 1: Use the dialog below to set the encoding of the source text file.





Set the text encoding of source file and include file.
However, if BOM is set in the input text file, BOM takes precedence.
When AUTO is set, text encoding is automatically determined.
The precompile output file is the same format as the source file.

2.1.2. Set Menu




Item	Content
Work Data	Set the work data name. (*1) Work data is a name that summarizes each setting content into one. The same operation can be performed by double-clicking the title bar of the main window.
Copy from other WorkData	Copy the setting contents from other work data.
Text Editor setting	Set information of the text editor to be activated when tag-jump.

*1: Set the work data name in the following dialog box.



2.1.3. Help Menu



Item	Content
Manual	Display SCANA's user's manual (this document)
Version	Show version of SCANA

2.1.4. Language Menu




Item	Content
Japanese	All menus and text etc. are displayed in Japanese
English	All menus and text etc. are displayed in English

* The language setting will be effective from the next startup

3. SOURCE FILE SETTING

When you select the "Source files" tab in the main window, the following screen will be displayed.



Here, set the C language source file to be analyzed.

If any source file is selected, the selected source file will be analyzed.

If neither source file is selected, all source files are analyzed.

Double-click (on any list box item) to deselect all items.

3.1. Setting of source file

Use one of the following methods to set the source file.

1) Drop the source file from Explorer into the list box of ①. (Convert to relative path when pressing Ctrl key)

2) From the Explorer, drop the folder containing the source file to the list box ①. (Convert to relative path when pressing Ctrl key)

In this case, the file specified by "wild card" in ② is set from the dropped folder and its subfolder group.

3) Right-click the list box in ① and set the source file from the "Edit item" menu with the following dialog.



When you press the "Select file" button, you can select the file by the file selection dialog.

Pressing the "Convert to relative path" button converts the selected source file to a relative path from "base folder".

It is OK even if you input the path name of the file directly in ③.


Press the "Update" button to add the set item.

3.2. Convert to Relative Path / Absolute Path

After selecting the item on the list box, right click and select "Convert selected item to relative path" / "Convert selected item to absolute path" menu, You can convert the path name of the source file to relative path or absolute path.


The relative path is relative to the folder set in "base folder".

Conversion example to relative path



3.3. Creating source text without comments

When you press the "Create source with comments removed" button at the bottom right of the source file setting screen, the following screen is displayed. You can create source file text with comments removed and words restructured.



Set the output folder and click the "Execution" button to create source text in the output folder with the comments removed from the source files set in the "Source files" tab.

If you check "Match line numbers to original source", line feed will be inserted and the line numbers will match the original source.


If you check "Align the start position of the line with the original source", the first column position of the line will match the original source.

For Example

Original source


```

1 : //-----//
2 : // Window Procedure //
3 : //-----//
4 : AJC_WNDPROC(Back, WM_CREATE )
5 : {
6 :     PWRKLISTBOX    pW;
7 :     BOOL            rc = -1;
8 :     RECT            r;
9 :     int             sty, exs;
10 :
11 :     do {
12 :         //----- Generate work space -----//
13 :         if ((pW = (PWRKLISTBOX) malloc(100) == NULL)
14 :             break;
15 :         memset(pW, 0, 100);
16 :         //----- Set my instance ID -----//
17 :         pW->InstID = INST_ID;
18 :     } while(0);
19 : }
    
```




```

1 : AJC_WNDPROC(Back, WM_CREATE)
2 : {
3 :     PWRKLISTBOX pW;
4 :     BOOL rc=-1;
5 :     RECT r;
6 :     int sty, exs;
7 :     do{
8 :         if ((pW=(PWRKLISTBOX) malloc(100))==NULL)
9 :             break;
10 :         memset(pW, 0, 100);
11 :         pW->InstID=INST_ID;
12 :     }while(0);
13 : }
    
```



```

1 :
2 :
3 :
4 : AJC_WNDPROC(Back, WM_CREATE)
5 : {
6 :     PWRKLISTBOX pW;
7 :     BOOL rc=-1;
8 :     RECT r;
9 :     int sty, exs;
10 :
11 : do{
12 :
13 :     if ((pW=(PWRKLISTBOX) malloc(100))==NULL)
14 :         break;
15 :     memset(pW, 0, 100);
16 :
17 :     pW->InstID=INST_ID;
18 : }while(0);
19 : }
    
```




```

1 :
2 :
3 :
4 : AJC_WNDPROC(Back, WM_CREATE)
5 : {
6 :     PWRKLISTBOX pW;
7 :     BOOL rc=-1;
8 :     RECT r;
9 :     int sty, exs;
10 :
11 :     do{
12 :
13 :         if ((pW=(PWRKLISTBOX) malloc(100))==NULL)
14 :             break;
15 :         memset(pW, 0, 100);
16 :
17 :         pW->InstID=INST_ID;
18 :     }while(0);
19 : }
    
```

* By removing the comments and reconstructing the token (place a single blank only where white space is needed), you can avoid inconsistencies due to differences in the number of comments and blanks in the SourceCompare tool.

4. PRE-COMPILE SETTING AND OPTION-SYMBOL / MACRO INFORMATION

When you select the "precompile setting" tab in the main window, the following screen will be displayed.



Here, we will make precompile related settings.


(Precompilation means resolving preprocessing statements such as "# include", "# define" and "#if".)

The setting contents are as follows.

#	Content
①	The symbols used in condition compilation (#if, #elif, #ifdef, #ifndef) are displayed. In case of unchecked, setting of ②~⑤ is invalid.
②	Display a list of symbol names.
③	The symbol and its reference point (file, line number) are displayed.
④	Exclude the symbols (#if, #elif, #ifdef, #ifndef) used in conditional compilation of the first line of the file.
⑤	Exclude symbols that contain a specific string. To specify more than one specific character string, separate them with a semicolon (;).
⑥	Displays a list of macros and references. In case of unchecked, setting of ⑦~⑩ is invalid.
⑦	Display a list of macro names.
⑧	It displays the macro and its reference point (file, line number).
⑨	Specify macros to exclude from display. <ul style="list-style-type: none"> · Empty : Exclude empty macros (macros without contents only with macro name, (ex. "#Define MACNAME")) · Simple : Exclude simple macros (macros without arguments, ex "#define MACNAME 123"). · Functional : Exclude functional macros (macro with arguments, ex '#define MACNAME (ARG, ...) ...').
⑩	Exclude macro names containing specific strings. To specify more than one specific character string, separate them with a semicolon (;).
⑪	Specify whether to include the contents of the include file in the output source file of the precompile result. When "Output expanded content of include file" is selected, include the contents of included file.
⑫	Automatically search include files from "Include pathes" and "base folder" including subfolders.
⑬	Do not read the same include file that has already been expanded.
⑭	A false condition is generated by conditional compilation, and the part that is not generated is also output to the file as a comment. (Add "//- " to the beginning of the line)
⑮	Suppresses precompile error messages. Choose whether to "suppress messages that include files can not be found" or "suppress all errors".

#	Content
⑮	Precompile header file (.h file)
⑰	If checked, check the file timestamps and do not precompile if the precompiled output file is newer than the source file. ※ Since the include file is not read by #include, the information such as macro name and type name defined in the include file is not output.
⑱	Set the precompile output destination folder as an include path. This include path has the highest priority and takes precedence over includes (#include "XXX.h") in the local folder.
⑲	Specify the output destination of the precompiled file. Precompile output files are created with the same file name in the same folder. (It does not create subfolders)
⑳	Specify an option symbol for precompilation. It is set from right-click popup menu. To set a value for a symbol, specify it in the format of "SYMBOL = value".
㉑	Specify an include path by one of the following methods. <ul style="list-style-type: none"> Drop a folder on this part. (If you hold down the Ctrl key while dropping it, it will be converted to a relative path) Set from right-click popup menu. If the check box (㉒) (include file automatic search) is checked, a wildcard can be specified as an include path. (Ex. "c:Program Files\Microsoft*.*)")

To precompile, check "Precompile" in the main window.



When "Check option symbol for condition compilation" is checked, "#if" "# elif" "# ifdef" "# ifndef" Display the referenced option symbol.

When "Display symbol list" is checked, a list of option symbol names is displayed.

When "Display symbol reference information" is checked, the reference position (file name, line number) of the option symbol is listed.

An example display of option symbol information is shown below.

Option symbols for pre-compile

[Option symbol list]

_Char_Is_Unsigned_	_KGLAVH_H	_KGLCTK_H	_KGLIHX_H	_KGLSUMW_H	_WIN64	KGL_XPRINT	KGLYMM_MH_T_UL
_CHAR_UNSIGNIED__	_KGLAVP_H	_KGLDEF_H	_KGLLSTH_H	_KGLSUMWR_H	AJC_DEFINED_BASICTYPE	KGLCIO_PRTFLEN	KGLYMM_MH_T_UW
_cpIusplus	_KGLCDL_H	_KGLFFH_H	_KGLLSTP_H	_KGLUSER_H	INT_MAX	KGLLST_NOSORT	KGLYMM_MHT_NUM
_K4	_KGLCIO_H	_KGLFFP_H	_KGLLZD_H	_KGLYMM_H	KGL_ALLOC	KGLPRT_L64	UNICODE
_MSC6	_KGLCOPT_H	_KGLFFO_H	_KGLPRT_H	_KGLYMM_H	KGL_DEFUCHAR	KGLSCLVAR_T	
_MSVC	_KGLCPS_H	_KGLFMM_H	_KGLRLB_H	_KGLXYM_H	KGL_INT16	KGLVALIDID_T64	
_VC80	_KGLCRAL_H	_KGLFSF_H	_KGLSJEUC_H	_KGLXYML_H	KGL_LITTLEENDIAN	KGLYMM_BSG1	
_CHAR_UNSIGNIED	_KGLCRAR_H	_KGLFSM_H	_KGLSTC_H		KGL_LLONG	KGLYMM_DBG1	
_DEBUG	_KGLCRCL_H	_KGLGSR_H	_KGLSTV_H	_MSC_VER	KGL_PTR64	KGLYMM_DBG2	
_KGL_SCL_H	_KGLCRDR_H	_KGLHSO_H	_KGLSUMB_H	_UNICODE	KGL_USEARG	KGLYMM_MH_T_UI	

[Option symbol reference list]

No.	Symbol	File-Path	Ref.Line
1:	_Char_Is_Unsigned_	"R:\MS_VS\kproj1*_gbl\INC\kglDEF.h"	106
2:	_CHAR_UNSIGNIED__	"R:\MS_VS\kproj1*_gbl\INC\kglDEF.h"	106
3:	_cpIusplus	"R:\MS_VS\kproj1*_gbl\INC\kglDEF.h"	320
4:	_K4	"R:\MS_VS\kproj1*_gbl\INC\kgluser.h"	5
5:	_MSC6	"R:\MS_VS\kproj1*_gbl\INC\kglDEF.h"	259
		"R:\MS_VS\kproj1\kgl*_GDL\SRC\kglVMM.c"	150
		"R:\MS_VS\kproj1\kgl*_GDL\SRC\kglFMM.c"	228
		"R:\MS_VS\kproj1\kgl*_GDL\SRC\kglGSR.c"	889
		"R:\MS_VS\kproj1\kgl*_GDL\SRC\kglVMM.c"	59 237 1593 1750 2357
6:	_MSVC	"R:\MS_VS\kproj1*_gbl\INC\kglAvP.h"	74
		"R:\MS_VS\kproj1*_gbl\INC\kglCps.h"	116 171
		"R:\MS_VS\kproj1*_gbl\INC\kglCtk.h"	247 283 318

} Indicate option symbols with #if, #elif, #ifdef and #ifndef.

When "Display macro information" is checked, information on macros detected at precompile time is displayed.

When "Display macro name list" is checked, a list of macro name names is displayed.

When "Display reference information of macro" is checked, the macro definition / reference place (file name, line number) is listed up.

An example of displaying macro information is shown below.

Macro names list

__DATE__ __TIME__ __TIMESTAMP__ _AJCAVLTREE_H_ _AJCDEF_H_ _AJCRINGBUF_H_ _AJRCHECKSUM_H_ _AJRCTL32_H_ _AJRCTLXX_H_ _MSC_VER ADDINDLLSECT AJC3DG_CLEAR_DATA AJC3DG_CLEAR_PLOT AJC3DG_MAXAXIS AJC3DG_MAXITEM AJC3DGM_GETBORDERCOLOR AJC3DGM_GETPROP AJC3DGM_NEEDNTC_ANGLE AJC3DGM_SETBORDERCOLOR AJC3DGM_SETPROP AJC3DGM_MAX_PLOTLIST : : :	AjcGetFolderNameEx AjcGetIniFileArr AjcGetIniFileBin AjcGetIniFileH64 AjcGetIniFileHex AjcGetIniFilePath AjcGetIniFileReal AjcGetIniFileS164 AjcGetIniFileSInt AjcGetIniFileStr AjcGetIniFileU164 AjcGetIniFileUInt AjcGetLastErrorText AjcGetMyPath AjcGetOpenFile AjcGetOpenFiles AjcGetOpenFilesEx AJCGETPF_ARR AJCGETPF_BIN AJCGETPF_HEX AJCGETPF_REAL	AJCPMG_WEDNESDAY AJCPMG_WEEKDAY AJCPMG_WEEKEND AjcPmgSetSchedInterval AjcPmgSetSchedTime AjcPmgSetSchedWeekly AjcPopUpMenu AJCPPOPUPMENU_H_ AJCPPOVMG_H_ AJCPPC_IFA_GEN AJCPPC_IFA_SKIP AJCPPC_INCKND_GBL AJCPPC_INCKND_LCL AJCPPC_INCKND_NO AJCPPC_MAX_IF_NEST AJCPPC_MAX_INC_NEST AJCPPC_PPK_ALL AJCPPC_PPK_COND AJCPPF_ACT_MISSING_INC AJCPPF_INC_AUTO_SEARCH AJCPPMF_EOT	AjcSetDlgPropU8 AjcSetDlgPropUI16 AjcSetDlgPropUI64 AjcSetDlgPropUInt AjcSetDlgValues AjcSetIniFilePath AjcSetProfilePath AjcSetRegMidPath AjcSetRegRootPath AJCSM AjcSMotToBin AjcSpPrintf AjcSpPrtSep AjcSpICreate AjcSpIEnumStr AjcSpIFind AjcSpIPartStrInPool AjcSpIPoolStrInStr AjcSpIRegist AjcSpIRemove	AJCVTHS_LOGFILE AJCVTHS_NOBORDER AJCVTHS_NOSCRL AjcVthSetDlgPropInt AJCVTHS_SEPARATE AjcVthSaveFont AjcVthSaveHtmlToFile AjcVthSaveProp AjcVthSetTextToFile AjcVthSearchAbove AjcVthSearchBelow AjcVthSetTitleText AjcVthSetTitleText AJCWINDOWITEM_H_ AJCWINDOWPORT_H_ AjcWriteBitmapToFile AjcYmCreate AjcYmFILEINFO AJCXYMODEM_H_ AJCXYN_ABORT AJCXYN_COMPLETE AJCXYN_END
--	--	--	---	---

Macro definition and reference information

No.	Macro Name	File-Path / Ref-Line	< Line >
			594
		"R:¥_Product¥AjrTerm¥AjrTerm¥AjrTerm¥src¥AjtWndTimeChart.c"	823
71:	AJC_WNDMAP_END	"R:¥_Product¥AjrTerm¥AjrTerm¥AjrTerm¥src¥AjtAbsPkt.h"	807
		"R:¥_Product¥AjrTerm¥AjrTerm¥AjrTerm¥src¥AjtAbsPkt.c"	807
		"R:¥_Product¥AjrTerm¥AjrTerm¥AjrTerm¥src¥AjtAbsTxt.c"	830
		"R:¥_Product¥AjrTerm¥AjrTerm¥AjrTerm¥src¥AjtMain.c"	1629 2049
		"R:¥_Product¥AjrTerm¥AjrTerm¥AjrTerm¥src¥AjtWnd2dGraphic.c"	809
		"R:¥_Product¥AjrTerm¥AjrTerm¥AjrTerm¥src¥AjtWnd3dGraphic.c"	610
		"R:¥_Product¥AjrTerm¥AjrTerm¥AjrTerm¥src¥AjtWndTimeChart.c"	640
72:	AJC_WNDMAP_MSG	"R:¥_Product¥AjrTerm¥AjrTerm¥AjrTerm¥src¥AjtAbsPkt.h"	806
		"R:¥_Product¥AjrTerm¥AjrTerm¥AjrTerm¥src¥AjtAbsPkt.c"	806
		"R:¥_Product¥AjrTerm¥AjrTerm¥AjrTerm¥src¥AjtAbsTxt.c"	829
			:
			:

Macro definition position

Macro reference place


4.1. header file precompilation

If the header file is huge and this header file is commonly included, it will take time to precompile the source files.

By precompiling the header file in advance, the precompile time of the source file can be shortened.

Follow the steps below to precompile the header file.

1) Press "Header (.h) file compilation" in ⑩ to display the following screen.



2) Make the following settings.

- Set the header file to be precompiled in part ①. (You can drop the header file)
- Set the include path required for precompilation in part ②. (You can drop the folder)
- In the part ③, specify the compile options required for precompilation. (Right-click to display the edit menu)

3) Click the "Precompile" button to execute precompilation. (If there is an error, it will be displayed in red in part ④)

4) Click the "Close" button to close the precompile screen of the header file.


5) Press ⑩'s "Set the precompile result output folder as the highest priority include path" button, and ⑪ precompile output destination.

Set the folder as the highest priority include path. (The folder is added to the "include path")

* Even if you manually add the ⑪ precompile output destination to the include path, it will not be the highest priority include path.

5. TYPE NAME INFORMATION

If you check "Show type name information" in the main window, information on the type name will be displayed.
 When "Type name list" is checked, a list of type names is displayed.
 When "Type definition list" is checked, the definition position of the type name is displayed.



Type names also include structure name (struct), union name (union), enumeration name (enum) in addition to the name defined by "typedef".

When you execute precompile, extract the precompile output source and the type name defined in the include file.
 If you do not want to precompile, extract the type name defined in the source program file.

An example display of type name information is shown below.

```

+-----+
| Type names |
+-----+

[ Type name list ]

ABSPKT      FILEINFO      PFILEINFO      PREP_TEXT      PWNDG3D      SHOW_ITEM      WNDG3D
ABSTXT      HORILINE      PHORILINE      PSNotifyScpEventAll  PWNDTMC      SNotifyScpEventAll  WNDTMC
CHARENCODE  PABSPKT      PKTDAT        PSYLITEM      REP_TEXT     SYLITEM
ECOMM       PABSTXT      PPKTDAT       PWNDG2D      RRRIND      WNDG2D

[ Type definition list ]


No.  Type Name      File-Path      < Line >
-----
1:  ABSPKT ----- "R:\_Product\AjrTerm\AjrTerm\AjrTerm\src\AjtAbsPkt.c" ----- < 34>
2:  ABSTXT ----- "R:\_Product\AjrTerm\AjrTerm\AjrTerm\src\AjtAbsTxt.c" ----- < 54>
3:  CHARENCODE ----- "R:\_Product\AjrTerm\AjrTerm\AjrTerm\src\AjtMain.c" ----- < 52>
4:  ECOMM ----- "R:\_Product\AjrTerm\AjrTerm\AjrTerm\src\Test.c" ----- < 18>
5:  FILEINFO ----- "R:\_Product\AjrTerm\AjrTerm\AjrTerm\src\AjtRecvModem.c" ----- < 28>
   ----- "R:\_Product\AjrTerm\AjrTerm\AjrTerm\src\AjtSendYModem.c" ----- < 27>
6:  HORILINE ----- "R:\_Product\AjrTerm\AjrTerm\AjrTerm\src\AjtWndTimeChart.c" ----- < 48>
7:  PABSPKT ----- "R:\_Product\AjrTerm\AjrTerm\AjrTerm\src\AjtAbsPkt.c" ----- < 34>
   :
   :
   :
    
```

} Type name Definition part

6. FUNCTION NAME INFORMATION

If you check "Display a list of function names" in the main window, a list of function names will be displayed. You can select "Internal function name list" and "External function name list" for function name list display. (You can also select 2)

When "Show internal function list" is checked, the definition position of the internal function, the number of instructions in the function, the number of keywords such as if and while, etc. are tabulated and displayed.



An example display of function name information is shown below.

```

-----/
| Func names
-----/

[ Internal function name list ]
AJC_DLGPROC(FileInput, IDCANCEL)      AJC_DLGPROC(MyDlg, WM_SCP_TXEMPTY)    AJC_WNDPROC(Back, ID_WND_3DPLOT)      FuncRecvModemIsOpened
AJC_DLGPROC(FileInput, IDOK)         AJC_DLGPROC(MyDlg, WM_SIZE)          AJC_WNDPROC(Back, ID_WND_MACRO)      FuncRecvModem
AJC_DLGPROC(FileInput, WM_INITDIALOG) AJC_DLGPROC(MyDlg, WM_TIMER)         AJC_WNDPROC(Back, ID_WND_TIMECHART)  FuncRecvModemIsBusy
AJC_DLGPROC(Relay, IDC_CMD_CREATE)   AJC_DLGPROC(Relay, IDC_CMD_OPEN)     AJC_WNDPROC(Back, IDC_YT100)         FuncRecvModemIsOpened
AJC_DLGPROC(Main, IDC_CMD_CONNECT)   AJC_DLGPROC(Relay, IDC_CMD_OPEN)     AJC_WNDPROC(Back, WM_CREATE)        FuncSendBinary
AJC_DLGPROC(Main, IDC_CMD_EASY)      AJC_DLGPROC(Relay, IDC_CMD_SETPORT)  AJC_WNDPROC(Back, WM_DESTROY)       FuncSendBinaryIsBusy
AJC_DLGPROC(Main, IDC_CMD_OPEN)      AJC_DLGPROC(Relay, IDCANCEL)         AJC_WNDPROC(Back, WM_DEVICECHANGE)   FuncSendFile
AJC_DLGPROC(Main, IDC_CMD_SEND)      AJC_DLGPROC(Relay, IDOK)            AJC_WNDPROC(Back, WM_ENDSESSION)     FuncSendFileIsBusy
:
:


[ External function name list ]
_max      AjcGetDlgItemCboIx      AjcRngPurse      AjcSin           CreateFile       MAjcSetDlgPropChk
_min      AjcGetDlgItemChk       AjcRngPutData    AjcSnPrintF     CreateMutex      MAjcSetDlgPropHex
_findclose AjcGetDlgItemHex4     AjcSaveDlgProfIles AjcStrCnvRevPath CreatePen        MAjcSetDlgPropReal
_findfirst AjcGetDlgItemHex      AjcSaveWndProc  AjcStrRetRevPath CreatePopupMenu  MAjcSetDlgPropStr
_findnext AjcGetDlgItemReal     AjcSaveWndRect  AjcSysTimeToTime1970 CreateSolidBrush MAjcSetDlgPropUIInt
_isimblead AjcGetDlgItemS164     AjcSbcComboBox  AjcTchEnableHLine CreateStatusWindow MAjcSetWindowLong
_isimbttrail AjcGetDlgItemSInt     AjcSbcLoadItems AjcTchGetDroppedFile CreateWindowEx   MAjcStrCat
_makepath AjcGetDlgItemStr     AjcSbcRadIDtns  AjcTchGetProp   DeleteDC         MAjcStrCmp
_splitpath _stat164              AjcGetDlgItemStrLen AjcSbcSaveItems AjcTchLoadPropEx DeleteFile       MAjcStrCpy
:
:

-----/
| Function definition information list
-----/
No.  Func.name      File-Path
# 1:  AjcDlgFileInput_IDCANCEL ----- "R:\_Product\WjrTerm\WjrTerm\src\WjtWnd2dGraphic.c" < 1129>
# 2:  " ----- "R:\_Product\WjrTerm\WjrTerm\src\WjtWnd3dGraphic.c" < 1113>
# 3:  " ----- "R:\_Product\WjrTerm\WjrTerm\src\WjtWndTimeChart.c" < 1825>
# 4:  AjcDlgFileInput_IDOK ----- "R:\_Product\WjrTerm\WjrTerm\src\WjtWnd2dGraphic.c" < 1085>
# 5:  " ----- "R:\_Product\WjrTerm\WjrTerm\src\WjtWnd3dGraphic.c" < 1070>
# 6:  " ----- "R:\_Product\WjrTerm\WjrTerm\src\WjtWndTimeChart.c" < 1282>
# 7:  AjcDlgFileInput_WM_INITDIALOG ----- "R:\_Product\WjrTerm\WjrTerm\src\WjtWnd2dGraphic.c" < 1030>
# 8:  " ----- "R:\_Product\WjrTerm\WjrTerm\src\WjtWnd3dGraphic.c" < 1015>
# 9:  " ----- "R:\_Product\WjrTerm\WjrTerm\src\WjtWndTimeChart.c" < 1227>
# 10: AjcDlgFileInput_WM_TIMER ----- "R:\_Product\WjrTerm\WjrTerm\src\WjtWnd2dGraphic.c" < 1064>
# 11: " ----- "R:\_Product\WjrTerm\WjrTerm\src\WjtWnd3dGraphic.c" < 1049>
# 12: " ----- "R:\_Product\WjrTerm\WjrTerm\src\WjtWndTimeChart.c" < 1261>
# 13: AjcDlgFileInputProc ----- "R:\_Product\WjrTerm\WjrTerm\src\WjtWnd2dGraphic.c" < 1142>
# 14: " ----- "R:\_Product\WjrTerm\WjrTerm\src\WjtWnd3dGraphic.c" < 1127>
# 15: " ----- "R:\_Product\WjrTerm\WjrTerm\src\WjtWndTimeChart.c" < 1339>
# 16: AjcDlgMain_IDC_CMD_CONNECT ----- "R:\_Product\WjrTerm\WjrTerm\src\WjtMain.c" < 1894>
# 17: AjcDlgMain_IDC_CMD_EASY ----- "R:\_Product\WjrTerm\WjrTerm\src\Test.c" < 210>
:
:

```

7. FUNCTION CALL STRUCTURE

By checking "Show function call structure" in the main window, analyze and display function call structure. If "Include external functions in the call structure" is checked, include external functions in function call structure.



An example display of the function call structure is shown below.

Function call structure

No.	Structure	File-Path	< Line >
# 288:	AjcDlgAddItem_IDOK	"R:\Ajrctrl_XX-XX-XX\Ajrctrl\Proj\src\Ajrctrl\XXX\AjcCtrlListBox.c"	< 1011>
	+ AjcGetDlgItemStrA ..#873		
	+ AjcLbxFindStringA ..#834		
	+ AjcLbxAddStringA ..#831		
	+ AjcLbxInsertStringA ..#863		
	+ SetHoriExtentByAllItem		
	+ GetHoriExtentByStrA		
	+ UpdHoriExtentByStrA		
	+ GetHoriExtentByStrA ...		
	+ AjcGetLangId ..#715		
	:		
	:		
# 673:	AjcGetDlgItemStrA	"R:\Ajrctrl_XX-XX-XX\Ajrctrl\Proj\src\Ajrctrl\XXX\AjcDlgItem.c"	< 75>
	+ AjcGetCtrlStrA ..#647		
# 674:	AjcGetDlgItemStrLenA	"R:\Ajrctrl_XX-XX-XX\Ajrctrl\Proj\src\Ajrctrl\XXX\AjcDlgItem.c"	< 95>
	+ AjcGetCtrlStrLenA ..#648		
# 675:	AjcGetDlgItemStrLenW	"R:\Ajrctrl_XX-XX-XX\Ajrctrl\Proj\src\Ajrctrl\XXX\AjcDlgItem.c"	< 100>
	+ AjcGetCtrlStrLenW ..#649		
	:		
	:		

Function definition position (file path name and line number)

".. # nnn" means that it is another top level function.

"..." already means that there is the same function in this structure.

When external functions are included in the calling structure, external functions are displayed in parentheses.

```

# 288: AjcDlgAddItem_IDOK ----- "R:\Ajrctrl_XX-XX-XX\Ajrctrl\Proj\src\Ajrctrl\XXX\AjcCtrlListBox.c" < 1011>
+ (GetProp)
+ AjcGetDlgItemStrA ..#873
+ AjcLbxFindStringA ..#834
+ (SendMessageA)
+ AjcLbxAddStringA ..#831
+ (SendMessage)
+ AjcLbxInsertStringA ..#863
+ SetHoriExtentByAllItem ----- "R:\Ajrctrl_XX-XX-XX\Ajrctrl\Proj\src\Ajrctrl\XXX\AjcCtrlListBox.c" < 1115>
| + (GetDC)
| + (SelectObject)
| + (SendMessageA)
+ GetHoriExtentByStrA ----- "R:\Ajrctrl_XX-XX-XX\Ajrctrl\Proj\src\Ajrctrl\XXX\AjcCtrlListBox.c" < 1187>
| | + (GetTextExtentPoint32A)
| | + (strlen)
| | + (_max)
| | + (ReleaseDC)
+ (EndDialog)
+ (GetDlgItem)
+ (SetFocus) ----- "R:\Ajrctrl_XX-XX-XX\Ajrctrl\Proj\src\Ajrctrl\XXX\AjcCtrlListBox.c" < 1147>
+ UpdHoriExtentByStrA
| + (GetDC)
| + (SelectObject)
| + GetHoriExtentByStrA ...
| + (SendMessageA)
| + (ReleaseDC)
+ (MessageBox)
+ AjcGetLangId ..#715
    
```

7.1. Tooltip display of top function name


When the cursor is placed on a function name, the top-level function name of the subfunction is displayed as tooltip text. (If the function is k-linked in multiple call trees, multiple top-level functions are displayed.)

```
# 491: WinMain -----
    +- AnlCmdLine -----
    +- Prologue -----
      | +- GetIniFilePathByDlg -----
      | +- SetIniPathMuteName -----
    +- OpenBackWindow -----
    +- ReserveWindowMinSize -----
    +- LoadAddinDll -----
    +- Epilogue -----
      WinMain
```

Display the top-level function name "WinMain" of Epilogue() with tooltip.

8. FUNCTION NAME EXTRACTION FILTER

When you select the "Function Name Extraction Filter" tab of the main window, the following windows are displayed and you can limit the name of the function to be collected.



Here, specify the condition of the function name to be collected.

The setting contents are as follows.

#	Content
①	Treat function names beginning with the specified character string as top level functions. (* 1)
②	Specifies a specific top level function group. <ul style="list-style-type: none"> · Add to the automatically detected top level function Add the function group specified by ① to the automatically detected top level function. · Specify a specific top level function We create a function call structure for only the function group specified by ①.
③	Collect function names starting with the specified character string.
④	Collects the function name including the specified character string.
⑤	Excludes function names beginning with the specified string.
⑥	Excludes the function name including the specified character string.
⑦	Include function names that do not contain lowercase letters ('a' - 'z') in the collection target. If unchecked, function names that do not contain lowercase letters ('a' to 'z') are excluded.
⑧	Activate the extraction filter condition of the function set in ①~⑦.
⑨	Invalidate the extraction filter condition of the function set in ①~⑦, and specify the extraction condition of the function with "Specific function".
⑩	Sort in ascending order of function name and output "internal function list" and "function call structure".
⑪	Setting macro to generate function name (This will be explained shortly).

To specify multiple strings in item ①, ③~⑥, separate them with a semicolon (;) and specify them.
Spaces before and after the specified character string are ignored.

* 1: Functions that have not been called from any source program are automatically recognized as top level functions.
"Function call structure" outputs the call structure in under of the top-level function, but by specifying another top-level function, the call structure is also output for that function.

Setting macro to generate function name

Suppose you have a function macro (AJC_WNDPROC) that generates a function name as follows.

```
#define AJC_WNDPROC(NAME, MSG) static LRESULT AjcWnd##NAME##_##MSG(HWND hwnd, UI msg, WPARAM wParam, LPARAM lParam)

AJC_WNDPROC(Main, WM_CREATE) ----- ①
{
    . . . . .
}

AJC_WNDPROC(Main, WM_SIZE) ----- ②
{
    . . . . .
}
```

The actual function name is generated by the AJC_WNDPROC () macro, and the actual function is ...

①= 'static LRESULT AjcWndMain_WM_CREATE(HWND hwnd,UI msg,WPARAM wParam,LPARAM lParam) '

②= ' static LRESULT AjcWndMain_WM_SIZE(HWND hwnd,UI msg,WPARAM wParam,LPARAM lParam) '

will be expanded .

If you do not precompile (or if a valid header file folder is not specified), the AJC_WNDPROC () macro will not be expanded and will interpret "AJC_WNDPROC" as a function name.

If there is the same function definition at several places like this, it will not be recognized even if you look at the reference.


In such a case, it can be set to treat it as a function name including the argument part.

①= ' AJC_WNDPROC(Main,WM_CREATE) '

②= 'AJC_WNDPROC(Main,WM_SIZE) '

as a function name.

To set it to treat it as a function name including the argument part, set the macro name with "Setting macro to generate function name" button.



In the list box, set a macro to generate a function name like "AJC_WNDPROC" above.


Note that "AJC_DLGPROC" and "AJC_WNDPROC" are set by default, so delete them if they are not convenient.

However, when precompiling and expanding these macros, it becomes the (original) function name generated by the macro, so it is not necessary to set the macro name.

8.1. SPECIFICATION OF SPECIFIC FUNCTION NAME

You can individually specify functions to be collected and top-level functions on the "Specific function" tab of the main window.

The setting on the "Function Name Extraction Filter" tab restricts the name of the function to be collected roughly, whereas on the "Specify Specific Function Name" tab, specify the name of each function directly.



The setting contents are as follows.


#	Content
①	Check to specify a specific function name. (Similar to checking "Specify a specific function" on the "Function extraction filter" tab)
②	Only specific function names are targeted. (Create function calling structure and cross-references of symbols only with the function group specified by ③)
③	When ② is checked, a specific function group to be targeted is enumerated. If ② is checked and nothing is specified, it becomes "no target function".
④	Exclude specific functions. (Exclude the function group specified by ⑤ from the function calling structure and cross-reference of symbols)
⑤	When ④ is checked, a specific function group to be excluded is enumerated. If ④ is checked and nothing is specified, all functions are covered.
⑥	Specifies a specific top level function group. <ul style="list-style-type: none"> Add to the automatically detected top level function Add the function group specified by ⑦ to the automatically detected top level function. Specify a specific top level function We create a function call structure for only the function group specified by ⑦.
⑦	Enumerate the specific top level functions in ⑥.

Only one of ② and ④ can be set.

⑦ specifies the name of the function to treat as the top level function.

9. SYMBOL CROSS REFERENCE INFORMATION

By checking "Display symbol list" in the main window, a list of collected symbols will be displayed. When "Show symbol reference information" is checked, cross-reference information of symbols is displayed.



Symbol cross reference information has the following three patterns.

#	Item	Content
1	Symbol -> Func	Lists the symbols and indicates the function referring to that symbol.
2	Func -> Symbol	List the function and indicate the symbol referenced in the function.
3	Top level func -> Symbol	Lists the functions of the highest level and shows the symbols used in the function including the called subfunction. That is, it shows the symbol to use when calling the top-level function.

9.1. Symbol -> Func

Lists the symbols and indicates the function referring to that symbol. An example display is shown below.

No.	Symbol	Function	File-Path / Ref-Line	< Line >
1:	_finddata_t	AjcDl\$MyDl\$_WM_INITDIALOG	"R:\$_Product\$AjrTerm\$AjrTerm\$AjrTerm\$src\$AjtAbsPkt.c"	< 99 >
		AjcDl\$MyDl\$_WM_INITDIALOG	"R:\$_Product\$AjrTerm\$AjrTerm\$AjrTerm\$src\$AjtAbsTxt.c"	< 130 >
		AjcDl\$MyDl\$_IDC_CMD_DELCND	"R:\$_Product\$AjrTerm\$AjrTerm\$AjrTerm\$src\$AjtAbsPkt.c"	< 428 >
		AjcDl\$MyDl\$_WM_INITDIALOG	"R:\$_Product\$AjrTerm\$AjrTerm\$AjrTerm\$src\$AjtAbsPkt.c"	< 99 >
		FAbPktReadProfileToVar	"R:\$_Product\$AjrTerm\$AjrTerm\$AjrTerm\$src\$AjtAbsPkt.c"	< 974 >
		FAbPktWriteProfileFromVar	"R:\$_Product\$AjrTerm\$AjrTerm\$AjrTerm\$src\$AjtAbsPkt.c"	< 1034 >
		Prologue	"R:\$_Product\$AjrTerm\$AjrTerm\$AjrTerm\$src\$AjtMain.c"	< 349 >
			395 395 396	
3:	AbstCondPkt	AjcDl\$MyDl\$_IDC_CMD_SELCOND	"R:\$_Product\$AjrTerm\$AjrTerm\$AjrTerm\$src\$AjtWnd2dGraphic.c"	< 778 >
		AjcDl\$MyDl\$_IDC_GRP_RXDATA	"R:\$_Product\$AjrTerm\$AjrTerm\$AjrTerm\$src\$AjtWnd2dGraphic.c"	< 814 >
		AjcDl\$MyDl\$_WM_SCP_RXPACKET	"R:\$_Product\$AjrTerm\$AjrTerm\$AjrTerm\$src\$AjtWnd2dGraphic.c"	< 781 >

Annotations in the image:
 - A red box highlights the 'Symbol name' column, with an arrow pointing to 'AbsPktPath' in the second row.
 - A red box highlights the 'Function referring to symbol and its defined position' column, with an arrow pointing to 'AjcDl\$MyDl\$_IDC_CMD_DELCND' in the second row.
 - A red box highlights the 'Reference line number' column, with an arrow pointing to '438' in the second row.

9.2. Func -> Symbol

List the function and indicate the symbol referenced in the function.
An example display is shown below.

Symbol reference information (Function -> Symbol)										
No.	Func. / Sym.	File-Path / Ref.Line	< Line >							
# 59:	AjcdIlgMyDlg_IDC_CMD_COPY	"R:_Product\AjrTerm\AjrTerm\AjrTerm\src\AjtAbsTxt.c"	< 659 >							
	hDlg	661								
	hVthSample	664								
	wParam									
# 60:	AjcdIlgMyDlg_IDC_CMD_DELCOND	"R:_Product\AjrTerm\AjrTerm\AjrTerm\src\AjtAbsPkt.c"	< 428 >							
	AbsPktPath	438								
	AppName	435								
	hDlg	430	435	436	440	441	442	445	447	447
	path	432	438	438	439					
	szCondName	438								
	szPrefix	438								
	wParam	434								
# 61:	AjcdIlgMyDlg_IDC_CMD_DELCOND	"R:_Product\AjrTerm\AjrTerm\AjrTerm\src\AjtAbsTxt.c"	< 409 >							
	AbsTxtPath	419								
	AppName	416								
	hDlg	411	416	417	421	422	423	426	428	428
	path	413	419	419	420					
	szCondName	419								
								


9.3. Top Level Func -> Symbol

Lists the functions of the highest level and shows the symbols used in the function including the called subfunction. That is, it shows the symbol to use when calling the top-level function.
An example display is shown below.

Symbol reference information (Top level Function -> Symbol)											
No.	Func. / Sym.	File-Path / Ref.Line	< Line >								
# 17:	AjcdIlgMain_IDC_CMD_SENDTEXT	"R:_Product\AjrTerm\AjrTerm\AjrTerm\src\AjtMain.c"	< 1935 >								
	hDlg	1943	1944	1945	1948	1949					
	hScp	1946									
	pTxt	1938*	1941*	1942	1943	1944	1945	1946	1947		
	wParam	1940									
# 18:	AjcdIlgMain_IDC_CMD_SETPORT	"R:_Product\AjrTerm\AjrTerm\AjrTerm\src\AjtMain.c"	< 1983 >								
	hWndBack	1986									
	wParam	1985									
	ShowLineInfo	"R:_Product\AjrTerm\AjrTerm\AjrTerm\src\AjtMain.c"	< 1983 >								
	BaudRate	3183									
	ByteSize	3185									
	TParity	3169									
	hScp	3161	3162	3168	3182	3190	3191				
	hWndSts	3163	3166	3187	3190	3191					
	Parity	3170									
	StopBits	3188	3188								
	szParity	3158	3171	3172	3173	3174	3175	3176	3180	3184	
	ShowFxError	"R:_Product\AjrTerm\AjrTerm\AjrTerm\src\AjtMain.c"	< 1983 >								
	ErrCntLBR	3144									
	ErrCntFE	3144									
	ErrCntIO	3144									
	ErrCntOE	3144									
	ErrCntPE	3144									
	hScp	3143									
	hWndSts	3145	3148								
# 19:	AjcdIlgMain_IDC_GRP_SHOWITEM	"R:_Product\AjrTerm\AjrTerm\AjrTerm\src\AjtMain.c"	< 1955 >								
	lParam	1960	1961	1962							
	SvlParam	1957*	1960	1961*							
	wParam	1959									
									

10. SYMBOL EXTRACTION FILTER

When you select the "Symbol extraction filter" tab in the main window, the following screen will be displayed.




The setting contents are as follows.

#	Content
①	Collects symbols starting with the specified string.
②	Collects symbols containing the specified string.
③	Excludes symbols beginning with the specified string.
④	Exclude symbols containing the specified string.
⑤	Excludes the specified symbol group
⑥	Exclude symbols that do not contain lower case letters ('a' ~ 'z').
⑦	Exclude symbols with N characters or less.
⑧	Exclude type name.
⑨	Exclude the function name.
⑩	Only the symbol reference inside the function is targeted.
⑪	Extract symbols from all input source files according to the condition of ① ~ ⑩
⑫	Specify a specific symbol. Specific symbols are set by the "Specific Symbol Specification" tab.

To specify multiple strings in item ①~⑤, separate them with a semicolon (;) and specify them. Spaces before and after the specified string are ignored.

10.1. SPECIFIC SYMBOL

When you select the "Specific symbol" tab in the main window, the following screen will be displayed.




The setting contents are as follows.

#	Content
①	Check to specify a specific function name. (Same as checking "Specify specific symbol" on the "Symbol extraction filter" tab)
②	Target a specific symbol group. (Create cross-references of symbols only with the symbol group specified by ③)
③	When ② is checked, a specific symbol group to be targeted is enumerated. If ② is checked and nothing is specified, it becomes "no target symbol".
④	Exclude certain symbol groups. (Exclude the symbol group specified by ⑤ from cross reference of symbols)
⑤	When ④ is checked, a specific symbol group to be excluded is enumerated. If ④ is checked and nothing is specified, all symbols will be covered.

Only one of ② and ④ can be set.

By specifying a specific symbol, you can display only the reference information of the specified symbol in "Symbol cross reference".

For example, when displaying the reference information of the symbols "hScp" and "hWndBack" in all the subfunctions under the Top level function, check "Specify a specific symbol" and "Specify valid symbols", and add "hScp" and "hWndBack" to ListBox



By pressing the "execution" button, we restricted it to the specified symbol. Output reference information of symbols.

```

+-----+
| Symbol reference information (Top level Function -> Symbol) |
+-----+

No.  Func. / Sym.                File-Path / Ref-Line                < Line >
. . . . .
#   21: AjcDlgMain_IDC_CMD_SETPORT ----- "R:\¥_Product¥AjrTerm¥AjrTerm¥AjrTerm¥src¥AjtMain.c" ----- < 2038>
      hScp ----- 2041
      hWndBack ----- 2041
      ShowLineInfo ----- "R:\¥_Product¥AjrTerm¥AjrTerm¥AjrTerm¥src¥AjtMain.c" ----- < 3276>
      hScp ----- 3282 3283 3289 3303 3311 3312
      ShowRxError ----- "R:\¥_Product¥AjrTerm¥AjrTerm¥AjrTerm¥src¥AjtMain.c" ----- < 3260>
      hScp ----- 3264
      . . . . .
  
```

From the above output, you can see that "hScp" and "hWndBack" are referenced by the top level function "AjcDlgMain_IDC_CMD_SETPORT", and "hScp" is referenced by its subfunction "ShowLineInfo" and "ShowRxError".

The calling structure of the function "AjcDlgMain_IDC_CMD_SETPORT" is as follows.


```

+-----+
| Function call structure |
+-----+

No.  Structure                File-Path                < Line >
. . . . .
#   21: AjcDlgMain_IDC_CMD_SETPORT ----- "R:\¥_Product¥AjrTerm¥AjrTerm¥AjrTerm¥src¥AjtMain.c" < 2038>
      +- ShowLineInfo ----- "R:\¥_Product¥AjrTerm¥AjrTerm¥AjrTerm¥src¥AjtMain.c" < 3276>
      +- ShowRxError ----- "R:\¥_Product¥AjrTerm¥AjrTerm¥AjrTerm¥src¥AjtMain.c" < 3260>
      . . . . .
  
```

11. SYMBOL CONFLICT INFORMATION

Checking "Show symbol conflict information" in the main window will list up the symbols referenced / updated in multiple top level function call structures under each top level function call structure.



For example, if you have the following function call structure, list the symbols referenced in multiple function structures under the four top-level functions "ist_ERI9", "ist_RXI9", "ist_TXI9" and "MainProc".

```

ist_ERI9
+- AjrRingPutByte


ist_RXI9
+- AjrRingPutByte

ist_TXI9
+- AjrRingGetByte

MainProc
+- MainInit
| +- InitEepRom
| +- DebugInit
|   +- AjrRingInit
|   +- DebugSendPacket
+- MainLoop
  +- DebugPeriod
  +- DebugPutS
  | +- AjrRingPutData
  +- DebugPrintF
    
```

※ The top-level function means a function (interrupt handler, task, etc.) that has not been called from within the program. However, functions that are dynamically called by function pointers and unused functions are also recognized as top-level functions.

In the example on the left, "MainProc" means main processing and "ist_XXXX" means an interrupt handler.



```

-----/
| Symbol conflict information (Symbol information conflicting between under the top level function group) |
|-----+
1 : RxRing - #46 MainProc "D:\work\AjrFW\AjrMaster\Src\AjrMain.c" - < 212>
   - #41 ist_ERI9 "D:\work\AjrFW\AjrMaster\Src\AjrDebug.c" < 540>
   - #42 ist_RXI9 "D:\work\AjrFW\AjrMaster\Src\AjrDebug.c" < 555>

2 : TxRing - #46 MainProc "D:\work\AjrFW\AjrMaster\Src\AjrMain.c" - < 212>
   - #43 ist_TXI9 "D:\work\AjrFW\AjrMaster\Src\AjrDebug.c" < 569>

3 : fTxBusy #4 #46 MainProc "D:\work\AjrFW\AjrMaster\Src\AjrMain.c" - < 212>
   #1 #43 ist_TXI9 "D:\work\AjrFW\AjrMaster\Src\AjrDebug.c" < 569>
    
```

"fTxBusy" means that it is referenced from two function call structures "MainProc" and "ist_TXI9". However, symbol update information is recognized only when updating symbols statically. If you are updating dynamically with a pointer etc., you can not recognize symbol updates. If the symbol has not been updated (or if the update can not be recognized), "-" is displayed.

When "Detail" is checked, the function name (under the top level function) that references / updates the symbol is also displayed.

Symbol conflict information (Symbol information conflicting between under the top level function group)					
1 : RxRing	-	#46	MainProc	-----	"D:\work\AjrFW\AjrMaster\Src\AjrMain.c" - < 212>
	-		DebugInit	-----	"D:\work\AjrFW\AjrMaster\Src\AjrDebug.c" < 88>
	-		DebugPeriod	-----	"D:\work\AjrFW\AjrMaster\Src\AjrDebug.c" < 125>
	-	#41	ist_ERI9	-----	"D:\work\AjrFW\AjrMaster\Src\AjrDebug.c" < 540>
	-	#42	ist_RXI9	-----	"D:\work\AjrFW\AjrMaster\Src\AjrDebug.c" < 555>
2 : TxRing	-	#46	MainProc	-----	"D:\work\AjrFW\AjrMaster\Src\AjrMain.c" - < 212>
	-		DebugInit	-----	"D:\work\AjrFW\AjrMaster\Src\AjrDebug.c" < 88>
	-		DebugPrintF	-----	"D:\work\AjrFW\AjrMaster\Src\AjrDebug.c" < 340>
	-		DebugPutS	-----	"D:\work\AjrFW\AjrMaster\Src\AjrDebug.c" < 317>
	-		DebugSendPacket	-----	"D:\work\AjrFW\AjrMaster\Src\AjrDebug.c" < 239>
	-	#43	ist_TXI9	-----	"D:\work\AjrFW\AjrMaster\Src\AjrDebug.c" < 569>
3 : fTxBusy	-	#46	MainProc	-----	"D:\work\AjrFW\AjrMaster\Src\AjrMain.c" - < 212>
	*1		DebugInit	-----	"D:\work\AjrFW\AjrMaster\Src\AjrDebug.c" < 88>
	*1		DebugPrintF	-----	"D:\work\AjrFW\AjrMaster\Src\AjrDebug.c" < 340>
	*1		DebugPutS	-----	"D:\work\AjrFW\AjrMaster\Src\AjrDebug.c" < 317>
	*1	#43	ist_TXI9	-----	"D:\work\AjrFW\AjrMaster\Src\AjrDebug.c" < 569>

Indicates that "fTxBusy" is referenced / updated by the four functions "DebugInit", "DebugPrintF", "DebugPutS" and "DebugSendPacket" under "MainProc".

※ I think that it is necessary to set the function name and the symbol name so as to exclude unnecessary names in "function extraction filter", "specific function", "symbol extraction filter" and "specific symbol".

In the output example shown above, the following settings are made.

Function extraction filter

Source files | Pre-compile setting | **Function extraction filter** | Specific function | Symbol extraction filter | Specific symbol

Function name extraction filter (Separate by semicolon (;) when multiple is specified)

First string of highest level function name:

Add to the automatically detected top level func

Specify a specific top level function

Target function names beginning with a specific string:

Symbol extraction filter

Source files | Pre-compile setting | Function extraction filter | Specific function | **Symbol extraction filter** | Specific symbol

Symbol extraction filter (Separate by semicolon (;) when specifying multiple)

Target symbols starting with a specific string:

Target symbols containing a specific string:

13. EXECUTABLE WINDOWS VERSION

SCANA can run on 32-bit platform (x86) and 64-bit platform (x64) in all versions (Windows 7, Windows 8, Windows 8.1, Windows 10) for Windows 7 and later for PC.
Executable files are as follows.

Type	Execution file	Note
Windows (32Bit)	SCAna32.exe	
Windows (64Bit)	SCAna64.exe	Executable only on 64Bit Windows

14. DISCLAIMER

Please pay attention to the following points when using the program.

- The copyright of SCANA belongs to the creator.
- Please use it in the user's responsibility in any case.
We can not assume any responsibility for operation results.